

5

Maintenance

List of Fluids and Lubricants

Item	Schedule	Grade	Cap.
Fuel	As needed.	Automotive Unleaded Gasoline	14 L (3.7 US gal)
Engine Oil	Fill Inspect daily. Fill as needed. Change Initially - After 20 hours of use. Every 50 hours afterwards. *2	Gasoline Engine Oil API rating: SE or better. SAE rating: 10W-30	1.4L (1.48 US qt) (1.7L)*1
Transmission Oil	Change Initially - After 50 hours of use. Every 500 hours afterwards.	Gear Oil API rating: GL-4 or 5 SAE rating: 80	0.9L (0.95 US qt)
Front Axle Oil	Change Initially - After 50 hours of use. Every 500 hours afterwards.	Gear Oil API rating: GL-4 or 5 SAE rating: 80	0.7L (0.74 US qt)
HST Oil	Change 2 years or every 300 hours (whichever comes first).	Gasoline Engine Oil API rating: SN/CF or better. SAE rating: 5W-40	4.0L (4.23 US qt)
Cutting Rotary Gearbox Oil	Change Initially - After 50 hours of use. Every 500 hours afterwards.	Gear Oil API rating: GL-4 or 5 SAE rating: 80	0.15L (0.16 US qt)
Battery Electrolyte	Fill Inspect every 50 hours and fill when necessary.	Distilled Water	-

*1 When replacing the oil filter cartridge.

*2 Our oil change interval is specific to this application and different from that in the Engine manual.
Follow our figure above.